

PRELIMINARY



FORTEC
GROUP

BLO-Line®

Blaze load optimized 4K monitors 64.5 inch — according to class A1

One partner, unlimited technology solutions

Product Features

Designed,
developed and
made in Germany

BLO-Line® 4K 64.5



BLO-Line® - PRODUCT OF THE YEAR 2024
Feuertrutz-Award in the category structural fire protection

Fire safety regulations prevent the installation of devices that increase fire load and promote the development of smoke gases. FORTEC Integrated has specifically developed a monitor series that offers optimal fire protection.

- BLO-Line® 4K monitors are fully functional units certified according to fire protection class A1, which means they meet the highest standards for fire protection.
- The certification was carried out based on the strictest European standards and verified and confirmed by independent experts.
- Our monitors are classified according to the European standard DIN EN13501-1 and fulfill the requirements of the VdS 6024 for fire protection of electrical devices in sensitive areas.
- Additional options such as integrated extinguishing devices make BLO-Line® 4K monitor ideal for use in public buildings such as hospitals, universities, schools, and airports.
- The monitors are available as regular monitors, IoT systems, or standalone systems with integrated PCs, they offer flexible application possibilities without expensive and heavy fireproof enclosures.
- BLO-Line® 4K monitors meet the strict smoke development requirements of the German MVVTrB:2024/01. While the TSP600s limit for MVVTrB is 35 m² and for the EU norm EN13501-1:2019-05 it is 50 m², BLO-Line with 21 m² is well below the requirements of both standards.

Our BLO-Line® 4K monitors are the perfect solution for maximum safety demands and easy installation. Trust the quality and reliability of FORTEC Integrated when it comes to fire protection in public areas.

Suitable for escape and rescue routes



Fire protection according to class A1

Fully functional unit is certified

Without additional fireproof enclosure

Fördermitglied im FORTEC Integrated is supporting member of
Bundesverband Brandschutz-Fachbetriebe e.V.
bvbfbf More about BLO: www.brandschutzmonitore.de

Panel and housing

	Measure	Description
Panel Diagonal & Pixel class	[mm] / [Inch]	1638/ 64.5 ISO 9241-307 (pixel error class II)
Type		BLO-Line monitor with glass or touch and bezel
Resolution	[Pixel]	3.840 x 2.160 (4K)
Luminance (center)	[cd/m²]	265 (Class F) 560 (Class G)
Viewing angle (U/ D/ L/ R)	[°]	89/ 89/ 89/ 89
Active area (H/V)	[mm]	1429 x 804
Backlight & Number of colors	... [M]	LED 16.7
Contrast ratio Response time (on/off)	... [ms]	4000:1 8
Life time back light until reaching half brightness	[h]	50.000
Continuous operating time	[h] / [d]	24/ 7
Mounting	[mm]	Wall mount included
Storage temperature	[°C] / [°F]	-20 ~ 60 / -4 ~ 140
Operating temperature	[°C] / [°F]	0 ~ 40/ 32 ~ 104
Storage & Operation humidity	[%]	10 ~ 90 (non condensing) 30 ~ 90 (non condensing)
Panel orientation		Versions in Landscape and Portrait
Location of connectors and OSD buttons		Connector: Front View right (Landscape), Front View top (Portrait) OSD: Front View left (Landscape), Front View bottom (Portrait)
Housing		Powdered steel sheet, black RAL 9005
Glass		Fire protection glass, 6.5 mm
Power supply	[V]	AC 110-240/ 50-60 Hz
Dimension (W x H x D)	[mm]	1494 x 868.5 x 101
Conformity		CE, FCC Class A, EU-RoHS, A1 according to EN13501-1
Packaging		Single packaging for one way pallet (max. 2 packages p.p.)
Package Contents		Safety instructions, power cable DB-07-607, BLO-Line® certificate, mounting instruction, energy classification label

BLO-Line® 4K 64.5



BLO-Line® 4K 64.5 monitor



BLO-Line® 4K 64.5 monitor with touch screen

All figures are typical values. The real values of the panel may vary. The optical characteristics are determined after the panel has been „ON“ for approximately 30 minutes at an ambient temperature of 25° C (77° F).

Life time of the backlight is defined as the time to take until the brightness reduces to 50% of its original value.

Prisma 4K Advanced - HDMI, DisplayPort



Order number Landscape		MO-41-247
Order number Portrait		MO-41-249
Interfaces		1x HDMI 1.4; 1 x HDMI 2.0; 1x DP 1.4; 1x Audio 3,5mm, USB B (Touch)
Weight	[kg]	66.6
Power consumption (typ.)	[Watt]	220

BLO-Line® 4K 64.5



BLO-Line® 4K 64.5 monitor backside incl. wall mount
(darker coloured for demonstration)


Options preview



Order number Landscape	MO-41-248	Touch monitor with Prisma 4K
Order number Portrait	MO-41-250	Touch monitor with Prisma 4K
Touch technology		PCAP touch, 10 touch points, projected capacitive
Glass		Fire protection glass 6.5 mm
Can be combined with		—

Touch integrated

IOT - Raspberry® IoT Controller



Order number Landscape		MO-41-257
Order number Portrait		MO-41-259
Interfaces		2x USB-A; 2x USB-C; 1x Audio 3,5mm; Micro-HDMI (4k, 60Hz); LAN RJ45
Raspberry® PI		CM3+, CM 4, 32 GB
Weight	[kg]	66.6
Power consumption (typ.)	[Watt]	250

BLO-Line® 4K 64.5



BLO-Line® 4K 64.5 IoT

Options preview



Order number Landscape	MO-41-258	Touch monitor with IoT
Order number Portrait	MO-41-260	Touch monitor with IoT
Touch technology		PCAP touch, 10 touch points, projected capacitive
Glass		Fire protection glass 6.5 mm
Can be combined with		—

Touch integrated

WebPoster

G

A
↑
G

BLO-Line® 4K 64.5

Order number Landscape		MO-41-251
Order number Portrait		MO-41-253
Interfaces		2x USB-A; 2x USB-C; 1x Audio 3,5mm; Micro-HDMI (4k, 60Hz); LAN RJ45
Weight	[kg]	66.6
Power consumption (typ.)	[Watt]	250

Options preview

G

A
↑
G

Touch integrated

Order number Landscape	MO-41-252	Touch monitor with WebPoster
Order number Portrait	MO-41-254	Touch monitor with WebPoster
Touch technology		PCAP touch, 10 touch points, projected capacitive
Glass		Fire protection glass 6.5 mm
Can be combined with		—

PC Intel® - Atom™

PRELIMINARY



Order number Landscape		MO-41-261
Order number Portrait		MO-41-263
Interfaces		1x DP, 1x USB-C, 2x LAN, 2x USB 3.2
PC		CPU: Intel® Atom™ 2x3,2GHz, RAM: 8 GB DDR5, Storage: 128 GB M.2 2242 SATA
Fan		no
Weight	[kg]	tbd
Power consumption (typ.)	[Watt]	tbd

BLO-Line® 4K 64.5



BLO-Line® 4K 64.5 IQ

Options

PRELIMINARY

Order number Landscape	MO-41-262	Touch monitor with IQ
Order number Portrait	MO-41-264	Touch monitor with IQ
Touch technology		PCAP touch, 10 touch points, projected capacitive
Glass		Fire protection glass 6.5 mm
Can be combined with		—

Touch integrated

Additional

Product	Order no.	Product description
Extinguishing cartridge	DS-92-079	Higher safety in cases of fire for all versions of BLO-Line®
Bezel with cable feedthrough	MO-41-xxx	Front bezel with outlet for cable feed BLO-Line® 4K 64.5, to cover the cable connections
Barcode Scanner	on request	Barcode Scanner in front behind the glass

Copyright 2026 FORTEC Integrated. Information in the document is subject to change without prior notice.

Our corporate network supports you worldwide with branches in Germany, Austria, Switzerland, the United Kingdom, the Netherlands, the Czech Republic, Egypt, and the United States. For further information, please contact:

CONTACT

FORTEC GROUP

FORTEC Elektronik AG | Augsburger Str. 2b | 82110 Germering
+49 89 894450-0 | info@fortecag.de | www.fortecag.de

FORTEC INTEGRATED

FORTEC Integrated GmbH | Augsburger Str. 2b | 82110 Germering
+49 89 894363-0 | info@fortec-integrated.de | www.fortec-integrated.de

FORTEC UNITED KINGDOM

FORTEC Technology UK Ltd. | Osprey House | 1 Osprey Court
Hinchingsbrooke Business Park | Huntingdon | Cambridgeshire | PE29 6FN
+44 1480 411600 | info@fortec.uk | www.fortec.uk

FORTEC EGYPT

FORTEC Electronic Design and Solutions Egypt SMLC | Linx Business Park | Unit B318
Smart Village | Giza Governorate
+20 120 1146222 | info@fortec.eg | www.fortec.eg

FORTEC CZECH REPUBLIC

FORTEC Czech Republic s.r.o. | Přátelství 275 | 330 02 Dýšina
+420 377 845878 | fortec@fortec.cz | www.fortec.cz

FORTEC POWER

FORTEC Power GmbH | Lise-Meitner-Straße 3 | 64560 Riedstadt
+49 6158 8285-0 | weborder@fortec-power.de | www.fortec-power.de

FORTEC UNITED STATES

FORTEC US, Corp. | 87 Raynor Avenue Unit 1 | Ronkonkoma | NY | 11779
+1 631 5804360 | info@fortec.us | www.fortec.us

FORTEC SWITZERLAND

FORTEC Switzerland AG | Bahnhofstraße 3 | 5436 Würenlos
+41 44 7446111 | info@fortec.ch | www.fortec.ch

FORTEC BENELUX

FORTEC Benelux B.V. | Everdenberg 79 | 4902 TT Oosterhout | North Brabant
+31 162 515458 | info@fortec-benelux.com | www.fortec-benelux.com